










CODE	TYPE	DRAWING		
16909	EF-40/1			
20564	EF-60/2			
SPARE PARTS	CODE DRAW.No.	DESCRIPTION	REF.	REMARK
	05710 107.1.517	<b>CONNECTION CABLE</b> dim.: 5X2,5mm <sup>2</sup> X1500		
	72055 TS-0645	<b>HEATING ELEMENT</b> power: 1800 W voltage: 230 V dim.: 318x78 mm		
	73477 TS-1017	<b>END SWITCH</b> el. load: 16A (4) 250V pole: 1		
	73101 TS-1019	<b>CONTACTOR DIL OOM-10</b> voltage: 230 V rated current: 20A		replaced with contactor 73112
	73454 TS-1011	<b>SWITCH ON-OFF</b> el. load: 16A/250V-10A/380V poles: 4		
	74155 TS-1016	<b>THERMOSTAT</b> operating temp.: 40-180°C el. load: 16 (4)A/380V pole: 1 capillary: L=1570 mm		replaced with thermostat 72553
	08262 107.2.292	<b>DRAIN TUBE</b> dim.: ∅ 19 / ∅ 22 mm		

electric fryers - spare parts

SPARE PARTS	CODE DRAW.No.	DESCRIPTION	REF.	REMARK
	42341 TS-0923	DRAIN VALVE 3/4"		
	73181 TS-1033	SAFETY-THERMOSTAT temperature limit: 218°C el. load: 20 (4)A/380V poles: 3 capillary: L= 2310 mm		replaced with safety- thermostat <b>72577</b>
	83287 TS-1018	HANDLE OF LID		replaced with handle of lid <b>83366</b> with special procedure
<b>MODIFICATION REALIZED: JULY 2003</b> - safety-thermostat 73181 is completely replaceable with safety-thermostat 72577 - thermostat 74155 is completely replaceable with s thermostat 72553				
	72577 TS-1365	SAFETY-THERMOSTAT temperature limit: 228°C el. load: 20 (4)A/380V poles: 3 capillary: L= 2210 mm		
	72553 TS-1364	THERMOSTAT operating temp.: 40-180°C el. load: 16 (4)A/380V pole: 1 capillary: L=1580 mm		
<b>MODIFICATION REALIZED: APRIL 2004</b> - handle of lid 83287 (screw 61015 M5x15) is replaceable with handle of lid 83366 only with following procedure: 1. cut of screw M5x15 2. drill a hole Ø 6 3. from lower side insert the screw M6x20 and screw up the handle of lid 83366				
	83366 TS-1369/2	HANDLE OF LID colour: black		
<b>MODIFICATION REALIZED: MARCH 2006</b> - contactor 73101 is completely replaceable with contactor 73112				
	73112 TS-1521	CONTACTOR DIL M7-10 voltage: 230 V	